



-  BSI accredited to BS EN3 & Kitemarked
-  Manufacturer's 5 year warranty
-  Stored pressure - Easy low cost maintenance
-  Safe if used in close proximity to electrical equipment
-  Suitable for A & B class fires
-  Controlled discharge
-  Brass valve - Easy to read pressure gauge
-  Powder coated, steel wire bracket



Ideal for use in vehicles and in industrial / commercial premises. Widely used in taxis, mini-buses, buses and other passenger carrying vehicles. Also very effective on fires caused by the combustion of flammable liquids and materials that liquefy such as plastic, oils, greases, paints, tar...

Safe, if used in error, on live electrical equipment, since the spray is non-conductive and complies with dielectric test to EN3-7 clause9. (Model tested to the BS EN3 35,000V dielectric test as defined by BSEN3-7:2004 ).

Refilling/Serviceing: Should be carried out annually to BS 5306 Part 3, 2009. After complete or partial use the extinguisher should be refilled to BS 6643 Part 1, 1985. Both refilling and servicing to be carried out by a competent person. Spares available on request.

Model	FBF2
Capacity	2 ltr
Total Weight	3.97 kg
Total Height	420 mm
Total Width (including bracket)	160 mm
Working Temp.	+5 <sup>o</sup> to +60 <sup>o</sup> C
Discharge Time	17 secs
Discharge Range	3-4 m
Operating Pressure	12 bar @ 20 <sup>o</sup> C
Minimum Burst Pressure	55 bar
Packing Specification	
Qty Per Carton	1
Carton Dimensions	44x13x13 cm
Carton Volume	0.008 m <sup>3</sup>
Carton Weight	4.1 kg
Qty Extinguishers per Pallet	180
Pallet Dimensions	120x100x143 cm
Pallet Volume	1.716 m <sup>3</sup>
Pallet Gross Weight	760 kg

