

**FBF6-M 6 ltr AFFF Foam**  
**FBF9-M 9 ltr AFFF Foam**

**Fire Rating 13A / 144B**  
**Fire Rating 21A / 183B**



-  BSI accredited to BS EN3 & Kitemarked
-  Manufacturer's 5 year warranty
-  Stored pressure - Easy low cost maintenance
-  Safe if used on electrical equipment
-  Suitable for A & B class fires
-  Controlled discharge
-  Brass valve - Easy to read pressure gauge
-  Protective plastic base
-  Supplied with wall-mounting bracket



Used in industrial and commercial premises, offices, petrol filling stations, chemical paint houses, boats, lorries... Also very effective on fires caused by the combustion of flammable liquids and materials that liquefy such as plastic, oils, greases, paints, tar...

Safe, if used in error, on live electrical equipment, since the spray is non-conductive and complies with dielectric test to EN3-7 clause9. (Model tested to the BS EN3 35,000V dielectric test as defined by BSEN3-7:2004 ).

Refilling/Service: Should be carried out annually to BS 5306 Part 3, 2009. After complete or partial use the extinguisher should be refilled to BS 6643 Part 1, 1985. Both refilling and servicing to be carried out by a competent person.

Spares available on request.

Model	FBF6	FBF9
Capacity	6 ltr	9 ltr
Total Weight	10.4 kg	14.5 kg
Total Height	550 mm	610 mm
Total Width (excluding hose)	220 mm	230 mm
Working Temp.	+5 <sup>o</sup> to +60 <sup>o</sup> C	+5 <sup>o</sup> to +60 <sup>o</sup> C
Discharge Time	30 secs	40 secs
Discharge Range	5-6 m	5-6 m
Operating Pressure	12 bar @ 20 <sup>o</sup> C	12 bar @ 20 <sup>o</sup> C
Minimum Burst Pressure	55 bar	55 bar
Packing Specification		
Qty Per Carton	1	1
Carton Dimensions	56x17x18 cm	62x20x20 cm
Carton Volume	0.017 m <sup>3</sup>	0.025 m <sup>3</sup>
Carton Weight	10.8 kg	15 kg
Qty Extinguishers per Pallet	70	48
Pallet Dimensions	120x100x134 cm	120x100x130 cm
Pallet Volume	1.608 m <sup>3</sup>	1.560 m <sup>3</sup>
Pallet Gross Weight	778 kg	742 kg

