



-  BSI accredited to BS EN3 & Kitemarked
-  Manufacturer's 5 year warranty
-  Stored pressure - Easy low cost maintenance
-  Suitable for A class fires
-  Controlled discharge
-  Brass valve - Easy to read pressure gauge
-  Protective plastic base
-  Supplied with wall-mounting bracket
-  Contents are neither harmful to people or damaging to the environment.

Suitable, fast and efficient for Class A fires fire involving combustible materials such as wood, paper, textiles and other carbonaceous materials.

Refilling/Service: Should be carried out annually to BS 5306 Part 3, 2009. After complete or partial use the extinguisher should be refilled to BS 6643 Part 1, 1985. Both refilling and servicing to be carried out by a competent person. Spares available on request.

Model	FBW9
Capacity	9 ltr
Total Weight	14.5 kg
Total Height	610 mm
Total Width (excluding hose)	230 mm
Working Temp.	+5 <sup>o</sup> to +60 <sup>o</sup> C
Discharge Time	55 secs
Discharge Range	6 m
Operating Pressure	12 bar @ 20 <sup>o</sup> C
Minimum Burst Pressure	55 bar
Packing Specification	
Qty Per Carton	1
Carton Dimensions	62x20x20 cm
Carton Volume	0.025 m <sup>3</sup>
Carton Weight	15 kg
Qty Extinguishers per Pallet	48
Pallet Dimensions	120x100x130 cm
Pallet Volume	1.560 m <sup>3</sup>
Pallet Gross Weight	742kg

