











-  BSI accredited to BS 7937 : 2000
-  Stored pressure
-  Suitable for A, B and F class fires
-  Safe if used in close proximity to electrical equipment
-  Controlled discharge
-  Brass valve - Easy to read pressure gauge
-  Protective plastic base
-  Supplied with wall-mounting bracket



wood, paper,
textiles



cooking oil
fat

 **A refillable fire extinguisher containing Wet Chemical, for use on Class F (cooking oil) fires in Fast Food Outlets, Fish & Chip Shops, Restaurants and other Catering establishments.**

Wet chemical fire extinguishers are not designed for use on electrical equipment, but in the modern kitchen environment, it is hard to avoid electricity cables. Hence, if the extinguisher is used in error on live electrical equipment, the spray of the Wet Chemical fire extinguisher is non-conductive, and passes the BS EN3 35,000V dielectric test as defined by BSEN3-7:2004).

Refilling/Serviceing: Should be carried out annually to BS 5306 Part 3, 2009. After complete or partial use the extinguisher should be refilled to BS 6643 Part 1, 1985. Both refilling and servicing to be carried out by a competent person.

Spares available on request.

Model	FBWC6
Capacity	6 ltr
Total Weight	10.7 kg
Total Height	610 mm
Total Width (excluding hose)	220 mm
Working Temp.	+5 ^o to +60 ^o C
Discharge Time	60 secs
Discharge Range	1-2 m
Operating Pressure	16 bar @ 20 ^o C
Minimum Burst Pressure	55 bar
Packing Specification	
Qty Per Carton	1
Carton Dimensions	63x19x19 cm
Carton Volume	0.022 m ³
Carton Weight	11.1 kg
Qty Extinguishers per Pallet	56
Pallet Dimensions	120x100x152 cm
Pallet Volume	1.824 m ³
Pallet Gross Weight	644 kg

