

LONG LIFE

Battery Operated Smoke Alarms FHB10 Series

FHB10

Sealed-in 10 year battery

FHB10W

Wireless interlink sealed optical alarm



The new and exciting range of optical smoke alarms comes with our unique **X-Profile** photoelectric chamber, controlled by bespoke software and featuring **TSE-Technology** (Thermal Stability Enhancement), specifically designed to reduce nuisance alarms while maximising the detection of smoke and fire.



- **AUTO SWITCH MOUNTING BASE PLATE.** Power automatically switched on when alarm is installed onto mounting plate and automatically switched off when alarm removed.
- Unique **X-Profile** detection chamber, protected by insect screen and controlled by bespoke software.
- **TSE-Technology** (Thermal Stability Enhancement) provides stability across a range of environmental conditions, reducing nuisance alarms whilst enhancing detection.
- **ALARM SILENCE BUTTON.** Ideal in non-emergency situations (nuisance alarms).
- **SILENCE 'low battery warning chirp' FUNCTION FOR UP TO 10 HOURS.** Maintains continuous protection during sleeping hours.
- **END OF ALARM LIFE INDICATION.**
- **APPROVED TO BS EN14604 : 2005 (FHB10).**
- **FHB10W - WIRELESS INTERLINK VERSION**



G211064



BS EN14604 : 2005
KM 623822

